

DT30L

SUZUKI 2 strokes motors , true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme operating conditions. These engines are perfect for equipping traditional fishing canoes. Suzuki's advanced technology provides fast starts, exceptional power, excellent fuel economy and smooth, quiet operation even at idle.



TECHNICAL CHARACTERISTICS	DT30L
MOTOR	
Engine Type	In-line 2
Trim method (positions)	Manual
Reverse direction	Front/Neutral/Rear
Steering Control	Tiller Handle
Gear Ratio	2.09:1
Ignition System	Manual
Maximum Power (Kw)	22.1(30)
Start-up	SUZUKI PEI
Fuel	Fuel and Oil
Max.Prop Shaft Horsepower (Kw)	5000-5600
Bore x Stroke (mm)	71 x 63
Displacement (cc)	499
MORE	
Propeller Rotation	Clockwise
Alternator	12V/30W
DIMENSIONS	
Engine Oil Capacity (L)	25
Dry weight with propeller (kg)	57,5
Engine transom height (mm)	508
Oil capacity (L)	1,5
EQUIPMENTS	
REGULAR PROPELLER (3 blades)	
Material	ALUMINUM
Diameter	10 1/4

Always wear a helmet, eye protection and protective proper clothing.
CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.