

SUZUKI 2-stroke engines offer greater power and the best possible performance combined with optimized fuel consumption. They are champions in their class and the best representatives of Suzuki's advanced technologies with incredible levels of performance on compact, lightweight and economical models.



TECHNICAL CHARACTERISTICS	DT9.9L
<b>MOTOR</b>	
Engine Type	In-line 2
Trim method (positions)	Manual
Reverse direction	Front/Neutral/Rear
Steering Control	Tiller Handle
Gear Ratio	1.92:1
Ignition System	SUZUKI PEI
Maximum Power (Kw)	7,3(9.9)
Start-up	Manual
Fuel	Fuel and Oil
Full throttle operating range (tr/min)	4500-5500
Bore x Stroke (mm)	59 x 52
Displacement (cc)	284
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	12V/80W
<b>DIMENSIONS</b>	
Engine Oil Capacity (L)	25
Dry weight with propeller (kg)	39,5
Engine transom height (mm)	508
Oil capacity (L)	0,8
<b>EQUIPMENTS</b>	
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	9 1/4

Always wear a helmet, eye protection and protective proper clothing.  
 CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.